


GEH SERIES



GEH...ES 2RS



Specifications

- Wider Inner Ring & larger OD – Capable of greater misalignment
- Sliding Surface: Steel on Steel - MoS₂ treated
- Single Fracture Design
- Relubricatable through annular grooves & oil holes in inner & outer rings (ES – Suffix)

Part #	Dimensions (mm)								Load Ratings kN		Weight LBS
	d	D	B	C	d _k	r _s min	r _{is} min	α ≈	Dynamic	Static	
GEH15ES	15	30	16	10	25	0.3	0.3	16	21	106	.108
GEH17ES	17	35	20	12	29	0.3	0.3	19	30	146	.183
GEH20ES	20	42	25	16	35.5	0.3	0.6	17	48	240	.337
GEH25ES	25	47	28	18	40.7	0.6	0.6	17	62	310	.450
GEH30ES	30	55	32	20	47	0.6	1	17	79	399	.670
GEH35ES	35	62	35	22	53	0.6	1	16	99	495	.900
GEH40ES	40	68	40	25	60	0.6	1	17	127	637	1.19
GEH45ES	45	75	43	28	66	0.6	1	15	156	780	1.57
GEH50ES	50	90	56	36	80	0.6	1	17	245	1220	2.51
GEH60ES	60	105	63	40	92	1	1	17	313	1560	4.50