



Unit	Shaft Dia.	Dimensions								Bearing	Housing	Weight	
No.		d	A	S	B	Bi	S1	P	E	W	No.	No.	kgs
SATRD205-14	7/8	1.88	0.34	1.17	1.20	0.91	3.00	2.60	0.78	SA205-14	TRD205	0.4	0.9
SATRD205-15	15/16	1.88	0.34	1.17	1.20	0.91	3.00	2.60	0.78	SA205-15	TRD205	0.4	0.9
SATRD205-16	1	1.88	0.34	1.17	1.20	0.91	3.00	2.60	0.78	SA205-16	TRD205	0.4	0.9
SATRD206-17	1 1/16	2.22	0.41	1.17	1.34	1.02	3.56	3.08	0.88	SA206-17	TRD206	0.6	1.4
SATRD206-18	1 1/8	2.22	0.41	1.17	1.34	1.02	3.56	3.08	0.88	SA206-18	TRD206	0.6	1.4
SATRD206-19	1 3/16	2.22	0.41	1.17	1.34	1.02	3.56	3.08	0.88	SA206-19	TRD206	0.6	1.4
SATRD206-20	1 1/4	2.22	0.41	1.17	1.34	1.02	3.56	3.08	0.88	SA206-20	TRD206	0.6	1.4
SATRD207-20	1 1/4	2.41	0.41	1.44	1.48	1.12	3.94	3.41	0.94	SA207-20	TRD207	0.8	1.8
SATRD207-21	1 5/16	2.41	0.41	1.44	1.48	1.12	3.94	3.41	0.94	SA207-21	TRD207	0.8	1.8
SATRD207-22	1 3/8	2.41	0.41	1.44	1.48	1.12	3.94	3.41	0.94	SA207-22	TRD207	0.8	1.8
SATRD207-23	1 7/16	2.41	0.41	1.44	1.48	1.12	3.94	3.41	0.94	SA207-23	TRD207	0.8	1.8