



Unit	Shaft Dia.	Dimensions										Bearing	Housing	Weight	
No.		d	L	J	A2	A1	A	S	N	B	H	Bi	No.	No.	kgs
SBFTD201-08	1/2	3.19	2.52	0.37	0.39	0.67	0.20	0.28	0.99	2.20	0.87	SB201-08G	PFTD203	0.23	0.51
SBFTD202-10	5/8	3.19	2.52	0.37	0.39	0.67	0.20	0.28	0.99	2.20	0.87	SB202-10G	PFTD203	0.23	0.51
SBFTD204-12	3/4	3.54	2.80	0.43	0.43	0.79	0.28	0.35	1.11	2.48	0.98	SB204-12G	PFTD204	0.27	0.59
SBFTD205-14	7/8	3.74	2.99	0.43	0.43	0.79	0.30	0.35	1.11	2.72	1.06	SB205-14G	PFTD205	0.38	0.84
SBFTD205-15	15/16	3.74	2.99	0.43	0.43	0.79	0.30	0.35	1.11	2.72	1.06	SB205-15G	PFTD205	0.38	0.84
SBFTD205-16	1	3.74	2.99	0.43	0.43	0.79	0.30	0.35	1.11	2.72	1.06	SB205-16G	PFTD205	0.38	0.84
SBFTD206-17	1 1/16	4.45	3.54	0.47	0.47	0.89	0.32	0.39	1.31	3.11	1.14	SB206-17G	PFTD206	0.54	1.19
SBFTD206-18	1 1/8	4.45	3.54	0.47	0.47	0.89	0.32	0.39	1.31	3.11	1.14	SB206-18G	PFTD206	0.54	1.19
SBFTD206-19	1 3/16	4.45	3.54	0.47	0.47	0.89	0.32	0.39	1.31	3.11	1.14	SB206-19G	PFTD206	0.54	1.19
SBFTD206-20	1 1/4	4.45	3.54	0.47	0.47	0.89	0.32	0.39	1.31	3.11	1.14	SB206-20G	PFTD206	0.54	1.19
SBFTD207-20	1 1/4	4.80	3.94	0.51	0.51	0.94	0.35	0.39	1.39	3.50	1.26	SB207-20G	PFTD207	0.71	1.56
SBFTD207-21	1 5/16	4.80	3.94	0.51	0.51	0.94	0.35	0.39	1.39	3.50	1.26	SB207-21G	PFTD207	0.71	1.56
SBFTD207-22	1 3/8	4.80	3.94	0.51	0.51	0.94	0.35	0.39	1.39	3.50	1.26	SB207-22G	PFTD207	0.71	1.56
SBFTD207-23	1 7/16	4.80	3.94	0.51	0.51	0.94	0.35	0.39	1.39	3.50	1.26	SB207-23G	PFTD207	0.71	1.56