



Unit	Shaft Dia.	Dimensions								Bearing	Housing	Weight		
No.		d	A	S	B	Bi	S1	P	E	W	No.	No.	kgs	lbs
SBTRD205-14	7/8	1.88	0.34	1.17	1.06	0.77	3.00	2.60	0.78	SB205-14	TRD205		0.3	0.6
SBTRD205-15	15/16	1.88	0.34	1.17	1.06	0.77	3.00	2.60	0.78	SB205-15	TRD205		0.3	0.6
SBTRD205-16	1	1.88	0.34	1.17	1.06	0.77	3.00	2.60	0.78	SB205-16	TRD205		0.3	0.6
SBTRD206-17	<sup>1</sup> 1/16	2.22	0.41	1.34	1.14	0.83	3.56	3.08	0.88	SB206-17	TRD206		0.3	0.7
SBTRD206-18	1 1/8	2.22	0.41	1.34	1.14	0.83	3.56	3.08	0.88	SB206-18	TRD206		0.3	0.7
SBTRD206-19	<sup>1</sup> 3/16	2.22	0.41	1.34	1.14	0.83	3.56	3.08	0.88	SB206-19	TRD206		0.3	0.7
SBTRD206-20	1 1/4	2.22	0.41	1.34	1.14	0.83	3.56	3.08	0.88	SB206-20	TRD206		0.3	0.7
SBTRD207-20	1 1/4	2.41	0.41	1.44	1.26	0.91	3.94	3.41	0.94	SB207-20	TRD207		0.7	1.6
SBTRD207-21	<sup>1</sup> 5/16	2.41	0.41	1.44	1.26	0.91	3.94	3.41	0.94	SB207-21	TRD207		0.7	1.6
SBTRD207-22	1 3/8	2.41	0.41	1.44	1.26	0.91	3.94	3.41	0.94	SB207-22	TRD207		0.7	1.6
SBTRD207-23	<sup>1</sup> 7/16	2.41	0.41	1.44	1.26	0.91	3.94	3.41	0.94	SB207-23	TRD207		0.7	1.6