



Unit No.	Shaft Dia. d	Dimensions										Set Screw	Bearing	Housing	Weight	
		L	J	A2	A1	A	S	N	B	Bi	H	ds UNF	No.	No.	kgs	lbs
UCFL201-8	1/2	4.45	3.54	0.59	0.43	1.00	0.50	0.45	1.31	1.22	2.36	1/4 28	UC201-08	FL204	0.48	1.06
UCFL202-10	5/8	4.45	3.54	0.59	0.43	1.00	0.50	0.45	1.31	1.22	2.36	1/4 28	UC202-10	FL204	0.48	1.06
UCFL204-12	3/4	4.45	3.54	0.59	0.43	1.00	0.50	0.45	1.31	1.22	2.36	1/4 28	UC204-12	FL204	0.48	1.06
UCFL205-14	7/8	5.12	3.70	0.63	0.51	1.06	0.56	0.45	1.41	1.34	2.68	1/4 28	UC205-14	FL205	0.6	1.32
UCFL205-15	15/16	5.12	3.70	0.63	0.51	1.06	0.56	0.45	1.41	1.34	2.68	1/4 28	UC205-15	FL205	0.6	1.32
UCFL205-16	1	5.12	3.70	0.63	0.51	1.06	0.56	0.45	1.41	1.34	2.68	1/4 28	UC205-16	FL205	0.6	1.32
UCFL206-17	1 1/16	5.83	4.61	0.71	0.51	1.22	0.63	0.45	1.58	1.50	3.15	1/4 28	UC206-17	FL206	0.9	1.98
UCFL206-18	1 1/8	5.83	4.61	0.71	0.51	1.22	0.63	0.45	1.58	1.50	3.15	1/4 28	UC206-18	FL206	0.9	1.98
UCFL206-19	1 3/16	5.83	4.61	0.71	0.51	1.22	0.63	0.45	1.58	1.50	3.15	1/4 28	UC206-19	FL206	0.9	1.98
UCFL206-20	1 1/4	5.83	4.61	0.71	0.51	1.22	0.63	0.45	1.58	1.50	3.15	1/4 28	UC206-20	FL206	0.9	1.98
UCFL207-20	1 1/4	6.34	5.12	0.75	0.55	1.34	0.69	0.51	1.75	1.69	3.54	5/16 24	UC207-20	FL207	1.2	2.64
UCFL207-21	1 5/16	6.34	5.12	0.75	0.55	1.34	0.69	0.51	1.75	1.69	3.54	5/16 24	UC207-21	FL207	1.2	2.64
UCFL207-22	1 3/8	6.34	5.12	0.75	0.55	1.34	0.69	0.51	1.75	1.69	3.54	5/16 24	UC207-22	FL207	1.2	2.64
UCFL207-23	1 7/16	6.34	5.12	0.75	0.55	1.34	0.69	0.51	1.75	1.69	3.54	5/16 24	UC207-23	FL207	1.2	2.64
UCFL208-24	1 1/2	6.89	5.67	0.83	0.55	1.42	0.75	0.51	2.02	1.94	3.94	5/16 24	UC208-24	FL208	1.6	3.52
UCFL208-25	1 9/16	6.89	5.67	0.83	0.55	1.42	0.75	0.51	2.02	1.94	3.94	5/16 24	UC208-25	FL208	1.6	3.52
UCFL209-26	1 5/8	7.40	5.83	0.87	0.63	1.50	0.75	0.59	2.06	1.94	4.25	5/16 24	UC209-26	FL209	1.9	4.18
UCFL209-27	1 11/16	7.40	5.83	0.87	0.63	1.50	0.75	0.59	2.06	1.94	4.25	5/16 24	UC209-27	FL209	1.9	4.18
UCFL209-28	1 3/4	7.40	5.83	0.87	0.63	1.50	0.75	0.59	2.06	1.94	4.25	5/16 24	UC209-28	FL209	1.9	4.18
UCFL210-30	1 7/8	7.76	6.18	0.87	0.63	1.57	0.75	0.59	2.15	2.43	4.53	3/8 24	UC210-30	FL210	2.2	4.84
UCFL210-31	1 15/16	7.76	6.18	0.87	0.63	1.57	0.75	0.59	2.15	2.43	4.53	3/8 24	UC210-31	FL210	2.2	4.84
UCFL210-32	2	7.76	6.18	0.87	0.63	1.57	0.75	0.59	2.15	2.43	4.53	3/8 24	UC210-32	FL210	2.2	4.84
UCFL211-32	2	8.82	7.24	0.98	0.71	1.69	0.87	0.65	2.30	2.20	5.12	3/8 24	UC211-32	FL211	3.1	5.82
UCFL211-34	2 1/8	8.82	7.24	0.98	0.71	1.69	0.87	0.65	2.30	2.20	5.12	3/8 24	UC211-34	FL211	3.1	5.82
UCFL211-35	2 3/16	8.82	7.24	0.98	0.71	1.69	0.87	0.65	2.30	2.20	5.12	3/8 24	UC211-35	FL211	3.1	5.82
UCFL212-36	2 1/4	9.84	7.95	1.14	0.71	1.89	1.00	0.65	2.70	2.56	5.51	3/8 24	UC212-36	FL212	4	8.8
UCFL212-37	2 5/16	9.84	7.95	1.14	0.71	1.89	1.00	0.65	2.70	2.56	5.51	3/8 24	UC212-37	FL212	4	8.8
UCFL212-38	2 3/8	9.84	7.95	1.14	0.71	1.89	1.00	0.65	2.70	2.56	5.51	3/8 24	UC212-38	FL212	4	8.8
UCFL212-39	2 7/16	9.84	7.95	1.14	0.71	1.89	1.00	0.65	2.70	2.56	5.51	3/8 24	UC212-39	FL212	4	8.8
UCFL213-40	2 1/2	10.16	8.27	1.18	0.79	1.97	1.00	0.91	2.74	2.56	6.10	3/8 24	UC213-40	FL213	5	11
UCFL214-44	2 3/4	10.43	8.50	1.22	0.79	2.13	1.19	0.91	2.97	2.94	6.30	7/16 20	UC214-44	FL214	4.5	10.9
UCFL215-47	2 15/16	10.83	8.86	1.34	0.79	2.20	1.31	0.91	3.09	3.05	6.50	7/16 20	UC215-47	FL215	6.2	13.64
UCFL215-48	3	10.83	8.86	1.34	0.79	2.20	1.31	0.91	3.09	3.05	6.50	7/16 20	UC215-48	FL215	6.2	13.64